






ALFA AC LED

BODY	Die cast aluminum
SOURCE	VOSSLOH ReadyLine COB (ON BOARD)
ELECTRIC EQUIPMENT	On/Off
CHARACTERISTICS	CRI 80 • Colour Consistency <3SDCM • LOR 92 • Power Factor 0,95 • Ingress protection IP 65
REGULATION	Manufactured in accordance with the Regulation EN 60598-1 and CE 93/68/EOK
AVAILABLE	Based on wall mounting (prefix A) • Και με βάση για επίτοιχη στήριξη (πρόθεμα A)



COLOUR TEMPERATURE KELVIN	4W		6W		8W	
	Lm	Lm/W	Lm	Lm/W	Lm	Lm/W
3000K	352	88	498	83	656	82
4000K	368	92	522	87	688	86

*Luminous flux & power consumption of led. Φωτεινή ροή & κατανάλωση πυρήνα led.

CODE*	WATT	KELVIN	CRI	REFLECTOR DEGREES	LED DRIVER	COLOUR
7028	4W (4)	3000K (3)	80 (8)	24° (24)	ON - OFF (C)	WHITE (-01)
	6W (6)					BLACK (-03)
	8W (8)	4000K (4)			BASE MOUNTING** (A)	ALUMINUM (-26)
						OTHER*** (-XX)
FINAL CODE						
7028	-- (WATT)	-- (KELVIN)	-- (CRI)	-- (REFLECTOR DEGREES)	-- (LED DRIVER)	- (COLOUR)

* To create the final product code add after their original prefix the **orange numbers or letters**, inside the parentheses, according to your choice. **Prefix "A" for based on wall mounting. ***Available in other colours, see page 10.