


LINEAR LIGHTS

ATLAS 6 LED

HIDDEN LIGHTING



A premium LED luminaire, with a high quality steel body. Suitable for professional and/or commercial spaces and stores. Available in White / Black / Anodized.

BODY

Steel, powder coated

SOURCE

PrevaLED Linear LED Module of European origin

ELECTRIC EQUIPMENT

Constant Current LED Driver: On/Off • Push Button
• Dali • Dim 1-10V with Dimmer • Emergency

OPTIC EQUIPMENT

PMMA Opal Diffuser

CHARACTERISTICS

CRI 80 • CCT 3000K - 4000K • Colour Consistency
3 - 4 SDCM • Ingress protection IP 20 • LOR 78 •
Power Factor 0,92

UPON REQUEST

Constant Lumen Operation • CRI 90

REGULATION

Manufactured in accordance with the Regulation EN 60598-1 and CE 93/68 EOK

SPECIAL APPLICATIONS

Combination of architectural and decorative lighting

CODE*	INSET	LENGTH (cm)	CRI	CCT	DRIVER	DIFFUSER
28	LOW (1)	058	80 (8)	3000 (30)	ON-OFF (C)	WITHOUT DIFFUSER (01)
		086			PUSH BUTTON (B)	
	MEDIUM (2)	114			1-10V (V)	
		142				
	HIGH (3)	170	90 (9)	4000 (40)	PHASE CUT (P)	WITH DIFFUSER (02)
		198			DALI (D)	
		226			SAFETY (S)	
FINAL CODE						
28	- (INSET)	- - - (LENGTH)	- (CRI)	- - (CCT)	- (DRIVER)	- - (DIFFUSER)

*To create the final product code add after their original prefix the orange numbers or letters, inside the parentheses, according to your choice.