


CYLINDER PENDANT LED

- BODY** Die cast aluminum
- SOURCE** Chip On Board (COB) LED Module • VOSSL0H ActiveLine LED Module • BRIDGELUX V10 (ON BOARD)
- ELECTRIC EQUIPMENT** On/Off • Push Button • Dali • Phase cut
- CHARACTERISTICS** CCT 3000K - 4000K • CRI 80 • Chromaticity < 3SDCM • Protection degree IP 20 • LOR 92 • Power Factor 0,97
- REGULATION** Manufactured in accordance with the Regulation EN 60598-1 and CE 93/68/EOK



CODE*	WATT	KELVIN	CRI	REFLECTOR DEGREES	LED DRIVER	COLOUR
11K	6,2W (6)	3000K (30)	80 (8)	12° (12)	ON - OFF (C)	WHITE (-01)
	9,3W (9)			25° (25)	DALI (D)	BLACK (-03)
	11,2W (1)	4000K (40)		36° (36)	PHASE CUT (P)	OTHER** (-XX)
FINAL CODE						
11K	--- (WATT)	-- (KELVIN)	-- (CRI)	-- (REFLECTOR DEGREES)	- (LED DRIVER)	- (COLOUR)

* To create the final product code add after their original prefix the **orange numbers or letters**, inside the parentheses, according to your choice. **Available in other colours, see page 10.

LED VOSSL0H ActiveLine LED Module



COLOUR TEMPERATURE KELVIN	6,2W @350mA		9,3W @350mA		11,2W @420mA	
	Lm	Lm/W	Lm	Lm/W	Lm	Lm/W
3000K	615	99	1200	129	1440	129
4000K	645	104	1252	135	1502	134

*Luminous flux & power consumption of led. Φωτεινή ροή & κατανάλωση πυρήνα led.