ELITE AC LED

BODY	Die cast aluminum
SOURCE	OSRAM AC PRO LED Module 230 V and VOSSLOH SCWABE (ON BOARD)
ELECTRIC EQUIPMENT	On/Off
CHARACTERISTICS	CRi 83 • LOR 92 • Power Factor 0,98 • Ingress protection IP 20
REGULATION	Manufactured in accordance with the Regulation EN 60598-1 and CE 93/68/EOK
AVAILABLE	Based on wall mounting (prefix A) • Και με βάση για επίτοιχη στήριξη (πρόθεμα A)
ACCESSORY	Barndoors, code 20-K038-468622 Honeycomb, code 272128



CODE*	WATT	KELVIN	CRI	REFLECTOR DEGREES	LED DRIVER	COLOUR
10	20W (20)	3000K (30)	80 (80)	12° (12)	ON - OFF (C)	WHITE (-01)
				24° (24)		BLACK (-03)
	33,3W (33)	4000K (40)		40° (40)	BASE MOUNTING** (A)	ALUMINUM (-26)
				60° (60)		OTHER*** (-XX)
FINAL CODE						
10	_ _ (WATT)	_ _ (KELVIN)	_ _ (CRI)	_ _ (REFLECTOR DEGREES)	_ (LED DRIVER)	- _ _ (COLOUR)

* To create the final product code add after their original prefix the orange numbers or letters, inside the parentheses, according to your choice. **Prefix "A" for based on wall mounting. ***Available in other colours, see page 10.

COLOUR TEMPERATURE KELVIN	20W		33,3W	
	Lm	Lm/W	Lm	Lm/W
3000	1816	91	2724	82
4000	1871	94	2806	84

*Luminus flux & power consuption of led. Φωτεινή ροή & κατανάλωση πυρήνα led.