




LARGE AC CUBE LED


BODY	Die cast aluminum
SOURCE	CUBE AC LED Module 230 V (ON BOARD)
ELECTRIC EQUIPMENT	Constant Current LED Driver: On/Off
CHARACTERISTICS	CRi>80 • LOR 90
REGULATION	Manufactured in accordance with the Regulation EN 60598-1 and CE 93/68/EOK
SPECIAL APPLICATIONS	Upon request with IP44 front protection



Cutting Hole Diameter 220 mm

CODE*	WATT	KELVIN	CRI	REFLECTOR DEGREES	LED DRIVER	COLOUR
33	17.6W (22)	3000K (30)	80 (80)	110° (110)	ON - OFF (C)	WHITE (-01)
						BLACK (-03)
	27W (31)	4000K (40)				ALUMINUM (-26)
						OTHER** (-XX)
FINAL CODE						
33	-- (WATT)	-- (KELVIN)	-- (CRI)	---- (REFLECTOR DEGREES)	-- (LED DRIVER)	- -- (COLOUR)

* To create the final product code add after their original prefix the **orange numbers or letters**, inside the parentheses, according to your choice. **Available in other colours, see page 10.



Κατόπιν παραγγελίας με μπροστινή προστασία IP44
Upon request with IP44 front protection

COLOUR TEMPERATURE KELVIN	17.6W	27W
	Lumen	Lumen
3000	2000	3000
4000	2000	3000

*Luminous flux & power consumption of led. Φωτεινή ροή & κατανάλωση πυρίνα led.