


MOUNTED ON CEILING



MARI 2 AC CUBE LED

BODY	Aluminum
SOURCE	OSRAM CUBE AC LED Module 230 V (ON BOARD)
OPTICAL MEDIUM	Aluminium reflector 110°
ELECTRIC EQUIPMENT	Constant Current LED Driver: On/Off • Dali • Push Button
CHARACTERISTICS	CCT 3000K 4000K • CRI 84 • Protection degree IP 20 • LOR 96 • Power Factor > 0,90
REGULATION	Manufactured in accordance with the Regulation EN 60598-1 and CE 93/68/EOK



CODE*	WATT	KELVIN	CRI	REFLECTOR DEGREES	LED DRIVER	COLOUR
72	18,8W (22)	3000K (30)	80 (80)	110° (110)	ON - OFF (C)	WHITE (-01)
						BLACK (-03)
		4000K (40)				ALUMINUM (-26)
						OTHER*** (-XX)
FINAL CODE						
72	-- (WATT)	-- (KELVIN)	-- (CRI)	-- (REFLECTOR DEGREES)	-- (LED DRIVER)	-- (COLOUR)

* To create the final product code add after their original prefix the **orange numbers or letters**, inside the parentheses, according to your choice. *** Available in other colours, see page 10.

COLOUR TEMPERATURE KELVIN	18,8W	30,4W
	Lumen	Lumen
3000	2000	3000
4000	2000	3000

*Luminous flux & power consumption of led. Φωτεινή ροή & κατανάλωση πυρήνα led.