



## CURVES

### RING

MOUNTED ON CEILING - SUSPENDED



SIDE. (cm)	69	97	125	153
	LUMEN			
3000 Kelvin	11430	17145	22860	28756
4000 Kelvin	12048	18072	24096	30120

CODE*	WATT	SIDE (cm)	CCT	DRIVER	COLORS
622	072	069	3000 (3)	ON-OFF (C)	WHITE (01)
	108	097			BLACK (03)
	144	125		PUSH BUTTON (B)	ANODIZED (26)
	180	153			WALNUT (52)
			4000 (4)	1-10V (V)	BIRCH (54)
				DALI (D)	WENGE (51)
				SAFETY (S)	MARBLE (53)
	FINAL CODE				
622	--- (WATT)	--- (DIAM.)	-- (KELVIN)	- (DRIVER)	-- (COLORS)

\*To create the final product code add after their original prefix the orange numbers or letters, inside the parentheses, according to your choice.

A premium square or rectangular LED luminaire, made of high quality extruded aluminum profile, which provides 120° continuous lighting.

Available in multiple dimensions and finishes (powder coated or anodized). Suitable for professional and/or commercial spaces and stores.

Code 96504 for mounting set, up to 1,5m long.

4 or more mounting sets required for suspended lights.

Available custom width of optical medium, upon request.

#### BODY

Aluminum, powder coated

#### SOURCE

PrevaLED Linear LED Module of European origin

#### ELECTRIC EQUIPMENT

Constant Current LED Driver: On/Off • Push Button • Dali • Dim 1-10V with Dimmer • Push Button

#### OPTIC EQUIPMENT

PMMA Opal Diffuser

#### CHARACTERISTICS

CRI 80 • CCT 3000K - 4000K • Colour Consistency <3SDCM • LOR 90 • Power Factor 0,96 • 50.000 hrs

#### REGULATION

Manufactured in accordance with the Regulation EN 60598-1 and CE 93/68 EOK

#### SPECIAL APPLICATIONS

Combination of architectural and decorative lighting

#### INSTALLATIONS

