



ROMA AC LED

BODY Die cast aluminum

SOURCE OSRAM AC PRO LED Module 230 V and VOSSLOH SCWABE (ON BOARD)

ELECTRIC EQUIPMENT On/Off

CRi 83 • LOR 92 • Power Factor 0,98 • Ingress protection IP 20 **CHARACTERISTICS**

REGULATION Manufactured in accordance with the Regulation EN 60598-1 and CE 93/68/EOK **AVAILABLE** Based on wall mounting (prefix A) • Και με βάση για επίτοιχη στήριξη (πρόθεμα A)

Barndoors, code 20-K038-468622 **ACCESSORY**




Honeycomb, code 272128









CODE*	WATT	KELVIN	CRI	REFLECTOR DEGREES	LED Driver	COLOUR					
13	20W (20)	3000K		12° (12)	ON - OFF	WHITE (-01)					
		(30)	80	24° (24)	(C)	BLACK (-03)					
	33,3W (30)	4000K	(80)	40° (40)	BASE MOUNTING**	ALUMINUM (-26)					
	40W (40)	(40)		60° (60)	(A)	OTHER*** (-XX)					
FINAL CODE											
13	— — (WATT)	— — (KELVIN)	CRI)	 _ (Reflector degree	S) (LED DRIVER)	 (COLOUR)					

^{*} To create the final product code add after their original prefix the orange numbers or letters, inside the parentheses, according to your choice. **Prefix "A" for based on wall mounting. ***Available in other colours, see page 10.

COLOUR TEMPERATURE	20W		33,3W		40W	
KELVIN	Lm	Lm/W	Lm	Lm/W	Lm	Lm/W
3000	1816	91	2724	82	3800	99
4000	1871	94	2806	84	3920	98

^{*}Luminus flux & power consuption of led. Φωτεινή ροή & κατανάλωση πυρήνα led.